109 FOREST NAPAVINE RD Arlie Champ LEWIS COUNTY CENTRAL SHOP

Chehalis, WA 98532

PHONE: 360-740-1150 FAX: 360-740-2685

SAMPLE SHIP TIME (days) SAMPLE TYPE: OIL

H330-49018-1025 LAB CONTROL NUMBER

SAMPLE DATE 17-Jan-2019

PROCESS DATE

EQUIPMENT METER

METER ON FLUID 487.0 HR

FLUID CHANGED Yes

MAKE UP FLUID

MAKE UP FLUID UNITS

FILTER CHANGED

Yes

12484.0 HR

18-Jan-2019

CUSTOMER EQUIP NUM COMPANY NAME: LEWIS COUNTY CENTRAL SHOP 21-105

COMPARTMENT NAME: ENGINE TRUCK SERIAL NUMBER R073126

JOB SITE MODEL T800B_KENWORTH MANUFACTURER

KENWORTH

EXT WARR NUMBER

COMP SERIAL NUM SHOP JOB NUM:

8813

EXT WARR EXPIRE DATE COMP MANUFACTURER COMPARTMENT MODEL FLUID BRAND/WEIGHT: SAMPLE LABEL NUM FUEL CONSUMED FLUID TYPE UNKNOWN

NC MACHINERY

No Action Required	H330-46274-1108	No Action Required	H330-47178-1095	No Action Required	H330-48109-1060	ı	No Action Required
WEAR METAL READINGS APPEAR NORMAL. OTHER ANALYSIS READINGS APPEAR TO BE ACCEPTABLE. CONTINUE SAMPLING AT THE NORMAL INTERVAL	28-Sep-2016 30-Sep-2016	THE OTHER PERSONS INCLUDED TO SERVICE OF SERVICES.	23-Jun-2017 27-Jun-2017 11507 HR THIS SAMPLE ADDEADS NODAMAL CONTINUE SAMPLING AT THE NODAMALINTERVAL	WEAR METAL READINGS APPEAR NORMAL. OTHER ANALYSIS READINGS APPEAR TO BE ACCEPTABLE, CONTINUE SAMPLING AT THE NORMAL INTERVAL	17-Apr-2018 19-Apr-2018		THIS SAMPLE APPEARS NORMAL. CONTINUE SAMPLING AT THE NORMAL INTERVAL
HER ANALYSIS READINGS APPEAR TO BE ACCEF	.2016 11008 HR	AMIL CING VI. THE MOUNDAY INTEXACT	2017 11507 HR	HER ANALYSIS READINGS APPEAR TO BE ACCER	2018 11997.0 HR		AMPLING AT THE NORMAL INTERVAL,
PTABLE. CONTINUE SAMPLING AT TH	522 HR Ye		499 HR Ye	PTABLE, CONTINUE SAMPLING AT TH	490.0 HR Ye		
HE NORMAL INTERVAL.	Yes		Yes	HE NORMAL INTERVAL.	Yes		
	Yes		Yes		Yes		

Oil Condition / Particle Count	H330-46274-1108	H330-47178-1095	H330-48109-1060	H330-49018-1025	Wear Me	
Oil Condition / Particle Count (ct/ml)	74-1108	78-1095	09-1060	18-1025	Wear Metals (ppm)	
ST	sa	2	8	o	C _L	
5-6	16	20	19	Z	n e	
IXO	=	**	*	.	ম	
NIT	4	ω	10		A	
	ω	103	-	ω	РЬ	
SUL	0	0	0	0	Sn	
×	7	o	01	O1	<u>co</u>	
	ы	0	12	ω	N	
>	0	0		ω	*	
,	9	œ	34	62	œ	
5	(cd	2	-	gn.	Mo	
V100	0	a	0	0	N.	
	0	0	0	0	Ag	
	4	-	_	4	п	
	0	0	0	o	<	
	0	0	0	0	Mn	
	0	0	0	0	Cd	
	2168	2020	1580	1285	Ca	
	18	15	413	638	Mg	
	1096	1158	1132	1166	Zn	
	937	984	1014	1022	ď	

0

Ва 0

H330-46274-1108 22 14 6	H330-47178-1095 22 13 6	H330-48109-1060 43 14 9	H330-49018-1025 33 14 9	
3 20	19	24	24	
z	z	Z	z	
z	z	z	z	
z	z	z	z	
ä	13.3	14.0	14.1	

Ag = Silver, Al = Alumnum, B = Boron, Ca = Calcium, Cr = Chomium, Cu = Copper, Fe = Iron, P = Phosphorus, K = Potassium, Li = Lithium, Mg = Magnesium, Mo = Molybdenum, Na = Sodium, Ni = Nickel, Pb = Lead, Si = Silicon, Sn = Tin, S = Sulphur, V = Vanadium, Zn = Zinc, A = Antifreeze, F = Fuel, W = Water, P = Postilive, N = Negative, T = Trace, E = Excessive, NIT = Nitration, OXI = Oxidation, ST = Soot, SUL = Sulfation, ISO = ISO Rating, PFC = Percent Fuel Content, PQI = Particle Quantifying index , NaW = Salt Water, FL Pt = Flash Point, TAN = Total Acid Number, TBN = Total Base Number, H2O = Karl Fisher result, V100 = Viscosity@100C, V40 = Viscosity@40C, PVI = Particle Volume Indicator

Notice: This analysis is intended as an aid in predicting mechanical wear. No guarantee, expressed or implied, is made against failure of this piece of equipment or a component thereof.